8550WLB[†] DC BATTERY BACKUP BELT DRIV WI-FI[®] GARAGE DOOR OPENER

Feature rich, offering ultimate garage protection.



SECURE

AUTOMATIC GARAGE DOOR LOCK CAPABLE: DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

TIMER-TO-CLOSE CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

SECURITY + 2.0[®] SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY myQ[®].

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

OUIET AND RELIABLE

BELT DRIVE SYSTEM AND QUIET DC MOTOR PROVIDE SMOOTH OPERATION AND LONG-LASTING SERVICE.

SOFT START/STOP FOR SMOOTH OPERATION.

INTEGRATED BATTERY BACKUP ENSURES GARAGE ACCESS EVEN WHEN THE POWER'S OUT.

WARRANTY LIFETIME MOTOR AND BELT, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

myQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

The State of California has not endorsed these or any other garage door openers. *8550W will transition to 8550WLB in mid 2019. *Requires additional purchase of myQ Home Bridge 819LMB. **Linking your myQ account to a partner may require an additional accessory purchase or subscription fee. Smartphone not included. Application screens may vary. Cellular data or Wi-Fi connection required. Test equipment regularly and follow safety instructions.

PRODUCT GUIDE 8550WLB DC BATTERY BACKUP BELT DRIVE WI-FI GARAGE DOOR OPENER

INCLUDED ACCESSORIES:



SMART CONTROL PANEL® LCD display enables simple programming and adjustment of settings.



3-BUTTON REMOTE CONTROL Operates up to 3 openers or myQ Light Accessories.



INTEGRATED BATTERY BACKUP Powers up the opener when the power's out.



POWERFUL ADD-ONS:

AUTOMATIC GARAGE DOOR LOCK CAPABLE Deadbolts the garage door automatically every time it closes.



825LN

REMOTE LIGHT CONTROL Plug in any lamp to this device



to control it with a smartphone or garage remote.



MINI UNIVERSAL **REMOTE CONTROL** Compact and portable to provide quick, easy garage access.



WIRELESS KEYLESS ENTRY Provides convenient, secure access from outside the garage with a 4-digit PIN.



LiftMaste

MASTERFUL ENGINEERING.

POWER -

-120V AC

-III Listed

-60 Hz Voltage

- 2.7A Current Rating

- 6' Power Cord (3-Prong)

MOTOR -

- -12V DC
 - -53 RPM
 - Automatic Thermal
 - Protection
 - Permanent Lubrication

MECHANICS

- Steel Chassis, T-Rail and Trolley
- Full Reinforced Belt Drive Mechanism (63:1 Gear Reduction and Adjustable Door Arm)
- Auto-Force Adjustment for Changing Weather and Environmental Conditions
- Electronic Limits for Easy Setup
- DC Wi-Fi Logic Board with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- -2 Lock Terminals Allow up to 2 Locks to Be Connected (Sold Separately)

STANDARD SPECS.

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200

.

Operating Temperature: -40°F to 150°F

- 3-Button Remote Control (893MAX)
- Remote Control: 310, 315 and 390 MHz Tri-Band** - Garage Door Opener: Frequency Agile on 310, 315
- and 390 MHz
- Anti-Burglary Coding
- **Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Smart Control Panel® (880LMW)

- Timer-to-Close
- Program Remote Controls, Keypads

HFAD

RAII

- and myQ Accessories
- Maintenance Alert System
- Easy Wi-Fi Setup

SHIPPING.

SHIPPING WEIGHT

(in lbs.)

CARTONS (3)

- CARTON 1: 19.81" x 11.94" x 11.19"
- Garage Door Opener Head (8550WLB)
- -Battery (485LM)
- Smart Control Panel (880LMW)
- 3-Button Remote Control (893MAX) - The Protector System® Safety Reversing Sensors
- CARTON 2: 10'4" x 5" x 5" (for 7' Rail)
- Assembled Solid-Steel Belt T-Rail
- CARTON 3 (OPTIONAL): 8" x 4.5" x 4"
- Automatic Garage Door Lock (841LM)

*8550W will transition to 8550WLB in mid 2019. [†]WARNING: to reduce the risk of injury to persons-ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door. © 2019 The Chamberlain Group, Inc. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group, Inc. 300 Windsor Drive, Oak Brook, IL 60523 LiftMaster.com

3 AUTOMATIC GARAGE DOOR LOCK (OPTIONAL)

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6'
Headroom Clearan	ce Rea	uired 2) ''

LiftMaster

Per second for door to move

> Per second for door

SPEED

(((902–928 MHz) 50-Channel FHSS

- communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone,

HOMELINK® COMPATIBLE

(VERSION 4.0 OR HIGHER***) May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

SAFETY AND SECURITY.

- Integrated Battery Backup
- Automatic Garage Door Lock Capable (2 Max.)
- Alert-2-Close/Unattended Close Operation⁺
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening

- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices

ALARM.COM is a registered service mark of Alarm.com. Apple is a trademark of Apple Inc., registered in the U.S. and other countries. HomeKit is a trademark of Apple Inc. Google, Google Home, Google Assistant and other related marks and logos are trademarks of Google Inc. Nest is a trademark of Nest Labs, Inc. XFINITY Home and the XFINITY Home design logo are trademarks or service marks of Comcast Corporation. UL® and the UL logo are trademarks of UL LLC © 2019 All Rights Reserved. Wi-Fi® is a registered trademark of Wi-Fi Alliance. HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation LMGDENPG8550WLB 2/19





(Frequency Hopping Spread Spectrum)

myQ[®] RADIO

- Provides 2-way
- tablet or computer.

g II





- Enhanced CFL
- (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

WI-FI® GARAGE DOOR OPENER

8 5 5 0 W L B*

DC BATTERY BACKUP BELT DRIVE



10